

三、QY80K 汽车起重机起重性能参数

表 1 主臂起重性能表 (kg, m)

全伸支腿 360° 作业, 12 吨平衡重										
幅度	12000	16130	20250	24380	28500	32630	36750	40880	45000	幅度
3000	80	62								3000
3500	73	57	42							3500
4000	67	53	42	32						4000
4500	60	49.5	42	32	30					4500
5000	54	46	41.6	32	30					5000
6000	45.5	41	36.8	28.5	27.6	25				6000
7000	38.5	36	33.4	26	24.5	23	20.5			7000
8000	31.2	30.6	30.2	24	23.4	21.5	18.6	15.5		8000
9000	25.1	24.6	24.3	22	21.7	20	17.2	14.5	12.6	9000
10000		20.3	20	20	19.5	17.8	15.8	14	12	10000
11000		17	16.7	17.7	18.3	16.5	14.6	13.1	11.6	11000
12000		14.4	14.1	15.1	15.8	15.2	13.4	12.3	11.4	12000
14000			10.4	11.3	11.9	11.7	11.5	10.6	10	14000
16000			7.7	8.6	9.3	9.2	9.5	9.1	8.2	16000
18000				6.7	7.3	7.3	7.6	7.9	7.6	18000
20000				5.2	5.8	5.9	6.2	6.4	6.4	20000
22000					4.6	4.7	5	5.3	5.3	22000
24000					3.6	3.8	4.1	4.3	4.4	24000
26000						3	3.3	3.6	3.6	26000
28000						2.3	2.7	2.9	3	28000
30000							2.1	2.3	2.4	30000
32000								1.8	1.9	32000
34000								1.4	1.5	34000
36000									1.1	36000
倍率	12	10	8	6	6	5	4	3	2	
使用吊钩	80t 吨吊钩 (1000kg)			40 吨吊钩 (360kg)						