

QAY400 主臂起重性能表 120 吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
3	400	235																				
3.5	265	225	198	198																		
4	235	216	197	196	194	193																
4.5	222	208	195	194	191	190	161	103	145													
5	212	195	185	184	180	179	160	102	145													
6	189	176	166	165	162	161	146	91	124	102	112	120										
7	172	158	150	149	146	145	136	95	127	98	105	111										
8	155	144	136	136	131	130	128	91	119	93	99	103	84	61	79							
9	136	130	125	124	121	120	117	87	110	88	92	94	78	58	74	63.5	58.6	63.1				
10	124	120	116	115	112	111	108	83	103	85	85	86	72	56	68	59.7	55.2	59.3	52.4	47.5		
12	102	99	98	97	93	92	93	75	89	78	76	74	63	51	60	53.0	49.3	52.6	46.9	42.7	39.8	35.3
14			86	85	82	81	83	69	79	70	64	63	55	46	52	47.6	44.5	47.2	42.3	38.7	37.2	32.8
16			75	75	70	69	69	61	67	65	57	55	49	42	46	43.1	40.5	42.7	38.5	35.3	34.0	30.1
18					62	61	60	54	57	59	52	49	44	39	41	39.3	37.0	38.9	35.2	32.4	31.3	27.6
20					56	54	54	51	51	53	47	44	39	37	38	36.1	34.1	35.6	32.3	29.9	28.8	25.5
22					50	48	49	48	47	45.5	40.2	37.4	36	34	35	33.2	31.6	32.7	29.9	27.7	26.8	23.7
24							43.7	45.9	43.0	42.2	36.9	34.3	33.5	32.8	32.4	30.8	29.4	30.3	27.7	25.9	24.9	22.1
							38.8	41.0	38.1	39.2	33.9	31.7	30.8	30.8	29.8	28.5	27.4	28.1	25.8	24.1	23.2	20.6
										35.9	31.5	29.2	28.5	29.0	27.6	26.7	25.7	26.2	24.1	22.6	21.7	19.2
										32.4	29.4	27.1	26.5	27.3	25.7	24.9	24.1	24.4	22.1	20.8	20.3	18.0
										29.4	27.5	25.2	24.6	25.7	24.0	23.3	22.7	22.8	20.7	19.7	18.7	17.0
													23.1	24.2	22.4	22.0	21.5	21.5	19.5	18.5	17.7	15.9

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													21.6	22.8	21.0	20.7	20.4	20.2	18.3	17.6	16.6	14.9
38																19.5	19.4	19.1	17.3	16.7	15.7	14.0
40																18.5	18.4	18.0	16.4	15.8	14.9	13.2
42																17.5	17.4	17.0	15.6	15.2	14.1	12.4
44																			14.8	14.5	13.3	11.7
46																			14.0	13.7	12.6	11.0
48																					12.1	10.6
50																					11.5	10.0
52																					10.9	9.4
54																						8.8
56																						8.2
臂长组合	0000	0000	0010	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~24		78~21	78~19
吊钩	240		210						140			80										
钩重	4.5 吨		3.55 吨						2.4 吨			1.15 吨										
说明	*为正后方作业																					

QAY400 主臂起重性能表 100 吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
3	400	235																				
3.5	265	225	198	198																		
4	235	216	197	196	194	193																
4.5	217	206	195	194	191	190	161	103	145													
5	204	194	185	184	180	179	160	102	145													
6	182	175	165	164	162	161	146	91	124	102	112	120										
7	164	157	148	147	146	145	136	95	127	98	105	111										
8	149	140	133	133	129	128	127	91	119	93	99	103	84	61	79							
9	132	126	122	121	118	117	117	87	110	88	92	94	78	58	74	63.5	58.6	63.1				
10	118	114	113	112	110	109	108	83	103	85	85	86	72	56	68	59.7	55.2	59.3	52.4	47.5		
12	98	95	94	93	90	89	90	72	86	78	76	74	63	51	60	53.0	49.3	52.6	46.9	42.7	39.8	35.3
14			80	79	78	77	77	65	75	70	64	63	55	46	52	47.6	44.5	47.2	42.3	38.7	37.2	32.8
16			69	68	66	65	65	57	63	64	56	54	49	42	46	43.1	40.5	42.7	38.5	35.3	34.0	30.1
18					57	56	56	50	53	56	49	46	44	39	41	39.3	37.0	38.9	35.2	32.4	31.3	27.6
20					51	49	51	48	48	50	44	41	38	36	37	36.1	34.1	35.6	32.3	29.9	28.8	25.5
22					46	43	45	45	44	42.5	37.2	34.4	34.8	33.4	33.5	33.2	31.6	32.7	29.9	27.7	26.8	23.7
24							39.1	41.5	38.3	39.2	33.9	31.3	32.5	31.8	31.4	30.8	29.4	30.3	27.7	25.9	24.9	22.1
26							34.5	36.9	33.7	35.7	30.4	28.2	29.8	29.8	28.8	28.5	27.4	28.1	25.8	24.1	23.2	20.6
28										31.9	27.5	25.2	27.5	28.0	26.6	26.7	25.7	26.2	24.1	22.6	21.7	19.2
30										28.4	25.4	23.1	25.5	26.3	24.7	24.9	24.1	24.4	22.1	20.8	20.3	18.0
32										25.4	23.5	21.2	23.6	24.7	23.0	23.3	22.7	22.8	20.7	19.7	18.7	17.0
34													22.1	23.2	21.4	22.0	21.5	21.5	19.5	18.5	17.7	15.9

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													20.6	21.8	20.0	20.6	20.4	20.2	18.3	17.6	16.6	14.9
38																18.8	19.4	18.4	17.3	16.7	15.7	14.0
40																17.1	18.2	16.7	16.4	15.8	14.9	13.2
42																15.6	16.7	15.2	15.6	15.2	14.1	12.4
44																			14.7	14.5	13.3	11.7
46																			13.5	13.7	12.6	11.0
48																					12.1	10.6
50																					11.5	10.0
52																					10.9	9.4
54																						8.8
56																						8.2
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~24		78~21	78~19
吊钩	240		210						140			80										
钩重	4.5 吨		3.55 吨						2.4 吨			1.15 吨										
说明	*为正后方作业																					

QAY400 主臂起重性能表 80 吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61	
3	300	235																					
3.5	242	225	198	198																			
4	225	216	197	196	194	193																	
4.5	211	204	192	191	184	183	161	103	145														
5	198	191	181	180	174	173	160	102	145														
6	177	173	162	161	156	155	146	91	124	102	112	120											
7	143	143	145	143	141	140	136	95	127	98	105	111											
8	131	131	131	131	127	126	122	90	119	93	99	103	84	61	79								
9	132	126	122	121	118	117	117	87	110	88	92	94	78	58	74	63.5	58.6	63.1					
10	110	110	111	110	108	106	104	81	101	85	85	86	72	56	68	59.7	55.2	59.3	52.4	47.5			
12	86	86	92	91	88	87	88	70	84	77	74	73	61	49	58	53.0	49.3	52.6	46.9	42.7	39.8	35.3	
14			70	71	71	69	70	63	69	68	63	62	53	44	50	47.6	44.5	47.2	42.3	38.7	37.2	32.8	
16			57	55	58	56	57	56	56	58	55	53	47	40	44	43.1	40.5	42.7	38.5	35.3	34.0	30.1	
18					48	46	47	48	46	48	48	45	42	37	39	39.3	37.0	38.9	35.2	32.4	31.3	27.6	
20					40	38	40	42	39	41	41	39	36	34	35	36.1	34.1	35.6	32.3	29.9	28.8	25.5	
22					34	32	34	37	34	35.6	35.0	33.4	32.8	31.4	31.5	33.2	31.6	32.7	29.9	27.7	26.8	23.7	
24							29.8	32.0	29.1	31.1	30.5	29.2	30.3	29.8	29.4	30.3	29.4	30.3	27.7	25.9	24.9	22.1	
26							26.1	28.3	25.4	27.4	26.8	25.5	26.6	27.8	26.8	26.6	27.4	28.1	25.8	24.1	23.2	20.6	
28										24.3	23.8	22.4	23.6	25.2	24.2	23.6	24.6	23.2	24.0	22.6	21.7	19.2	
30										21.7	21.2	19.8	21.0	22.6	21.6	21.0	22.0	20.6	21.4	20.8	20.3	18.0	
32										19.4	18.9	17.6	18.7	20.3	19.4	18.7	19.8	18.4	19.2	19.7	18.7	17.0	
34													16.8	18.4	17.4	16.8	17.8	16.4	17.2	18.5	17.7	15.9	

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													15.1	16.7	15.7	15.1	16.1	14.7	15.5	16.8	16.2	14.9
38																13.6	14.6	13.2	14.0	15.3	14.7	14.0
40																12.8	13.9	12.4	13.3	14.6	14.0	13.2
42																11.6	12.6	11.2	12.0	13.3	12.7	12.4
44																			10.9	12.2	11.6	11.6
46																			9.9	11.2	10.6	10.6
48																					9.6	9.7
50																					9.0	9.0
52																					8.2	8.2
54																						7.5
56																						6.8
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~24		78~21	78~19
吊钩	240		210						140			80										
钩重	4.5 吨		3.55 吨						2.4 吨			1.15 吨										
说明	*为正后方作业																					

QAY400 主臂起重性能表 60吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61	
3	229	229																					
3.5	212	212	198	198																			
4	197	197	188	188	181	180																	
4.5	185	185	176	176	170	169	158	101	142														
5	174	174	167	166	160	159	154	99	142														
6	155	155	149	148	143	142	138	89	122	100	109	117											
7	140	140	134	133	130	129	125	93	124	96	103	109											
8	127	127	122	122	118	117	113	88	113	91	97	101	82	60	77								
9	110	110	112	111	109	107	104	84	104	87	90	92	77	57	72	60.3	55.7	60.0					
10	98	98	104	102	100	99	96	79	96	83	83	85	71	55	67	56.7	52.4	56.3	49.8	45.2			
12	69	69	71	70	73	70	72	68	71	73	72	71	60	48	56	50.4	46.8	50.0	44.6	40.6	37.8	33.5	
14			57	56	58	56	57	60	56	59	58	57	52	43	49	45.2	42.3	44.9	40.2	36.8	35.4	31.2	
16			46	44	48	46	47	50	46	48	48	46	46	39	43	41.0	38.5	40.6	36.6	33.5	32.3	28.6	
18					38	36	37	39	36	38	37	36	37	36	38	37.2	35.2	36.8	33.4	30.8	29.7	26.3	
20					33	31	33	35	32	34	33	32	33	33	34	33.2	32.4	32.7	30.7	28.4	27.4	24.2	
22					29	27	28	30	27	29.1	28.6	27.1	28.3	30.0	29.0	28.3	29.4	27.9	28.4	26.3	25.4	22.5	
24							23.9	26.2	23.2	25.2	24.7	23.3	24.5	26.1	25.1	24.5	25.6	24.1	24.9	24.6	23.6	20.9	
26							20.7	23.0	20.0	22.0	21.5	20.1	21.3	23.0	21.9	21.3	22.4	20.9	21.7	22.9	22.14	19.6	
28										19.4	18.8	17.5	18.6	20.3	19.3	18.6	19.7	18.2	19.1	20.4	19.8	18.2	
30										17.1	16.6	15.2	16.4	18.0	17.0	16.4	17.5	16.0	16.8	18.2	17.5	17.1	
32										15.2	14.7	13.3	14.5	16.1	15.1	14.5	15.5	14.1	14.9	16.2	15.6	15.6	
34													12.8	14.4	13.4	12.8	13.9	12.4	13.2	14.5	13.9	14.0	

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													11.3	12.9	12.0	11.4	12.4	11.0	11.8	13.1	12.5	12.5
38																10.1	11.1	9.7	10.5	11.8	11.2	11.2
40																8.9	9.9	8.5	9.3	10.6	10.0	10.1
42																7.9	8.9	7.5	8.3	9.6	9.0	9.0
44																			7.4	8.7	8.1	8.1
46																			6.5	7.8	7.2	7.3
48																					6.6	6.6
50																					5.9	5.9
52																					5.2	5.3
54																						4.7
56																						4.1
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~24		78~21	78~19
吊钩	240		210						140			80										
钩重	4.5 吨		3.55 吨						2.4 吨			1.15 吨										
说明	*为正后方作业																					

QAY400 主臂起重性能表 40 吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61	
3	222	222																					
3.5	206	206	194	194																			
4	192	192	183	183	176	175																	
4.5	179	179	172	171	165	164	155	99	139														
5	168	168	161	161	156	155	149	97	139														
6	150	150	144	143	140	139	134	87	119	98	107	115											
7	135	135	131	130	126	125	122	91	121	94	101	107											
8	123	123	119	118	115	113	111	86	110	89	95	99	80	58	76								
9	95	95	101	99	102	99	101	82	100	85	88	91	75	56	71	59.1	54.6	58.8					
10	76	76	82	81	84	81	83	78	82	81	82	82	70	54	66	55.6	51.4	55.2	48.8	44.3			
12	53	53	59	58	61	58	59	62	59	61	60	59	59	47	55	49.4	45.9	49.0	43.7	39.8	37.1	32.8	
14			45	44	47	44	46	48	45	47	46	45	46	42	47	44.3	41.4	44.0	39.4	36.0	34.7	30.6	
16			36	35	37	35	36	39	35	38	37	35	37	39	37	36.7	37.7	36.3	35.9	32.8	31.7	28.0	
18					31	28	29	32	29	31	30	29	30	32	31	30.0	31.2	29.6	30.5	30.2	29.1	25.7	
20					25	23	24	27	24	26	25	24	25	27	26	25.0	26.1	24.6	25.5	26.8	26.2	23.7	
22					21	19	21	23	20	21.8	21.3	19.8	21.0	22.8	21.7	21.1	22.2	20.6	21.5	22.9	22.2	22.1	
24							17.4	19.7	16.6	18.7	18.1	16.7	17.9	19.6	18.6	17.9	19.0	17.5	18.4	19.7	19.1	19.1	
26							14.8	17.1	14.0	16.1	15.5	14.1	15.3	17.0	16.0	15.3	16.4	14.9	15.8	17.1	16.5	16.5	
28										13.9	13.4	12.0	13.2	14.8	13.8	13.2	14.2	12.8	13.6	14.9	14.3	14.4	
30										12.1	11.5	10.2	11.3	13.0	12.0	11.4	12.4	11.0	11.8	13.1	12.5	12.5	
32										10.5	10.0	8.6	9.8	11.4	10.4	9.8	10.8	9.4	10.2	11.5	10.9	10.9	
34													8.7	10.4	9.4	8.7	9.8	8.3	9.2	10.5	9.9	9.9	

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													7.5	9.1	8.1	7.5	8.6	7.1	7.9	9.3	8.6	8.7
38																6.4	7.5	6.0	6.9	8.2	7.5	7.6
40																5.6	6.6	5.1	6.0	7.4	6.7	6.8
42																4.7	5.7	4.2	5.1	6.5	5.8	5.9
44																			4.3	5.7	5.0	5.1
46																			3.7	5.1	4.4	4.5
48																			3.0	4.4	3.7	3.8
50																					3.1	3.2
52																					2.5	2.6
54																						2.0
臂长 组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂 仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~24		78~ 21	78~ 19
吊钩	240		210					140			80											
钩重	4.5 吨		3.55 吨					2.4 吨			1.15 吨											
说明	*为正后方作业																					

QAY400 主臂起重性能表 0 吨平衡重,支腿全伸 9.5 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
3	209	209																				
3.5	172	172	164	164																		
4	161	161	154	153	147	146																
4.5	150	150	144	143	138	138	133	97	132													
5	141	141	135	134	130	130	125	96	125													
6	101	101	99	99	96	95	92	80	92	89	89	89										
7	60	60	60	59	62	59	60	63	59	62	61	60										
8	44	44	44	42	45	43	44	46	43	45	45	43	44	46	45							
9	32	32	34	32	35	33	34	36	33	35	34	33	34	36	35	34	35	34				
10	26	26	27	26	28	26	27	29	26	28	28	26	27	29	28	27	28	27	28	29		
12	16	16	18	17	19	17	18	20	17	18	19	17	18	20	19	18	19	18	19	20	19	20
14			11.9	11.7	12.3	12.1	12.5	13.5	12.3	12.9	12.6	12.4	13.4	14.9	14.0	13.4	14.4	13.1	13.8	15.0	14.4	14.5
16			8.2	8.0	8.6	8.4	8.8	9.7	8.6	9.1	8.9	8.7	9.7	11.1	10.3	9.7	10.6	9.4	10.1	11.2	10.7	10.7
18					5.9	5.8	6.2	7.0	6.1	6.5	6.3	6.1	7.1	8.4	7.6	7.1	8.0	6.8	7.5	8.5	8.0	8.1
20					4.8	4.5	5.0	5.7	4.8	5.4	5.1	4.9	6.4	6.8	6.6	6.2	6.5	6.0	6.3	6.5	6.9	7.0
22					3.5		3.6	4.5	3.4	4.2	3.8	3.5	5.0	5.4	5.2	4.9	5.2	4.6	4.9	5.4	5.5	5.5
24							2.1	3.0		2.7	2.4		3.4	3.8	3.6	3.2	3.6	3.0	3.4	3.9	4.1	4.1
26													2.1	2.5	2.3	2.1	2.3		2.3	2.7	2.9	3.0
28																				2.0	2.0	2.0

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~36			78~46			78~26			78~49			78~55		78~59	78~61
吊钩	210						140						80									
钩重	3.55 吨						2.4 吨						1.15 吨									
说明	*为正后方作业																					

QAY400 主臂起重性能表 60 吨平衡重,支腿全伸 6.23 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
3	210	203																				
3.5	201	187	178	177																		
4	187	174	165	165	158	158																
4.5	175	161	154	153	148	147	141	101	140													
5	165	150	144	143	139	138	132	99	132													
6	147	126	121	120	116	115	111	89	111	100	108	107										
7	133	112	108	107	105	103	100	93	99	96	97	96										
8	121	88	88	87	87	86	83	84	83	81	81	80	78	60	77							
9	104	68	68	67	69	67	68	70	67	69	69	67	68	57	68	60.3	55.7	60.0				
10	93	56	57	55	58	56	57	59	56	58	58	56	57	55	58	56.7	52.4	56.3	49.8	45.2		
12	65	42	42	41	43	41	42	44	41	43	43	41	42	44	43	42.5	43.5	42.1	42.9	40.6	37.8	33.5
14			35	33	36	34	35	37	34	36	36	34	35	37	36	36.3	36.3	34.9	35.7	36.8	35.4	31.2
16			28	27	29	27	28	30	27	29	29	27	28	30	29	28.4	29.4	28.0	28.8	30.0	29.4	28.6
18					24	22	23	25	22	24	24	22	23	25	24	23.3	24.3	23.0	23.7	24.9	24.3	24.4
20					21	19	20	22	20	21	21	20	21	22	21	20.7	21.7	20.3	21.1	22.4	21.8	21.8
22					18	16	17	19	16	18.1	17.6	16.4	17.4	19.0	18.1	17.5	18.4	17.1	17.9	19.1	18.5	18.5
24							14.3	16.4	13.7	15.5	15.0	13.7	14.8	16.4	15.4	14.8	15.8	14.5	15.2	16.5	15.9	15.9
26							12.2	14.2	11.5	13.3	12.9	11.6	12.7	14.2	13.3	12.7	13.6	12.3	13.1	14.3	13.7	13.7
28										11.5	11.0	9.8	10.8	12.4	11.4	10.9	11.8	10.5	11.3	12.5	11.9	11.9
30										10.0	9.5	8.2	9.3	10.8	9.9	9.3	10.3	9.0	9.7	10.9	10.3	10.4
32										8.6	8.1	6.9	8.0	9.5	8.6	8.0	8.9	7.6	8.4	9.6	9.0	9.0
34													6.8	8.3	7.4	6.8	7.8	6.5	7.2	8.4	7.8	7.9

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													5.8	7.3	6.4	5.8	6.8	5.4	6.2	7.4	6.8	6.9
38																4.9	5.8	4.5	5.3	6.5	5.9	6.0
40																4.1	5.0	3.7	4.5	5.7	5.1	5.1
42																3.4	4.3	3.0	3.8	4.9	4.4	4.4
44																			3.1	4.3	3.7	3.8
46																					3.1	3.2
48																					2.6	2.6
50																					2.1	2.1
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~21			78~29		78~26	78~32
吊臂仰角	66~19		69~24		73~19		75~23			75~18			75~22			75~19			75~26		75~24	75~30
吊钩	210									140			80									
钩重	3.55 吨									2.4 吨			1.15 吨									
说明	*为正后方作业																					

QAY400 主臂起重性能表 40 吨平衡重,支腿全伸 6.23 米

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
3	210	195																				
3.5	206	179	170	170																		
4	192	166	158	158	151	150																
4.5	179	150	143	143	138	137	132	99	132													
5	168	141	135	134	129	128	124	97	123													
6	150	118	113	113	110	108	105	106	105	98	102	101										
7	135	93	93	91	95	92	93	91	92	92	92	91										
8	123	64	64	63	65	63	64	67	64	66	65	64	65	58	66							
9	95	52	52	50	53	51	52	54	51	53	53	51	52	54	53	52.4	53.5	51.9				
10	76	40	40	39	41	39	40	42	39	41	41	39	41	42	41	40.6	41.6	40.2	41.0	42.3		
12	53	29	29	28	30	28	29	31	29	30	30	29	30	31	30	29.6	30.6	29.3	30.0	31.2	30.6	30.7
14			22	21	23	21	22	24	22	23	23	22	23	24	23	22.7	23.6	22.3	23.0	24.2	23.6	23.7
16			17	16	18	17	17	18	17	18	18	17	18	19	18	17.9	18.8	17.5	18.2	19.3	18.8	18.8
18					17	13	14	14.3	13	15	15	13	14	16	15	14.4	15.2	14.0	14.7	15.8	15.3	15.3
20					14	12	13	13.4	12	14	14	12	13	15	14	13.4	14.3	13.0	13.8	15.0	14.4	14.4
22					11	10	10	11.0	10	10.8	10.5	9.9	10.9	11.6	10.9	11.0	11.9	10.6	11.3	12.0	12.0	12.0
24							8.5	9.0	7.9	8.8	8.6	8.0	9.0	9.7	9.0	9.0	9.1	8.6	9.4	10.1	10.0	10.0
26							6.9	7.4	6.3	7.2	7.0	6.4	7.4	8.0	7.4	7.4	7.5	7.0	7.8	8.4	8.4	8.4
28										5.9	5.6	5.0	6.0	6.7	6.0	6.0	6.2	5.7	6.4	7.1	7.0	7.1
30										5.0	4.8	4.1	5.2	5.9	5.2	5.2	5.4	4.8	5.6	6.3	6.2	6.3
32										4.0	3.7	3.0	4.1	4.8	4.1	4.1	4.3	3.8	4.5	5.2	5.2	5.2
34													3.4	4.2	3.4	3.4	3.6	3.0	3.8	4.6	4.5	4.5

幅度	15.5*	15.5	20.7	20.7	26	26	31.2	31.2	31.2	36.4	36.4	36.4	41.7	41.7	41.7	46.9	46.9	46.9	52.1	52.1	57.4	61
36													2.5	3.3	2.6	2.6	2.8	2.2	3.0	3.7	3.6	3.7
38																2.0			2.2	3.0	2.9	2.9
40																				2.3	2.2	2.2
臂长组合	0000	0000	0100	1000	0110	1100	1110	0111	1200	1111	1120	2110	2111	1112	1211	2211	1221	2220	2221	1222	2222	3333
倍率	22	22	19	19	19	19	16	10	14	10	10	12	8	7	7	6	6	6	5	5	4	3
吊臂仰角	77~30		78~33		80~25		80~28			78~23			78~26			78~33			78~37		78~44	78~47
吊钩	210						140						80									
钩重	3.55 吨						2.4 吨						1.15 吨									
说明	*为正后方作业																					